








ASTORI CALL OUT		SIZES	FIELD OF APPLICATION AND MATERIALS			REFERENCE STANDARDS		NOTES
ANCHOR NUTS ONE LUG								
	PO100	6-32÷5/16	900MPa	235°C	25CrMo4	MS21051	NAS682	
	PO101		900MPa	425°C	A286	MS21052	NAS682	
	PO102		1100MPa	235°C	25CrMo4	NAS1771		
	PO103		1100MPa	425°C	A286	NAS1771C		
	O100	3÷10	900MPa	235°C	25CrMo4	LN29673		
	O101	4÷8	900MPa	425°C	A286	LN29692		
	O110	3÷10	900MPa	235°C	25CrMo4	LN29984	LN65130	
	O111		900MPa	425°C	A286	LN29992	LN65133	
	JO120		1100MPa	235°C	25CrMo4	DIN65347	EN2753	
	JO121		1100MPa	425°C	A286	DIN65346	EN3539 EN4248	
JO127	6÷10	1100MPa	315°C	A286	JN0411		EMC, deep c'bore	
	O130	4÷6	900MPa	235°C	25CrMo4	LN29674		100°countersunk
	O131	8-32÷1/4	900MPa	425°C	A286	LN29689		
	PO130		900MPa	235°C	25CrMo4	MS21053-	NAS683	
	PO131		900MPa	425°C	A286	MS21054	NAS683	
	O140	5÷6	900MPa	235°C	25CrMo4			variable deep c'bore
	O141	10-32÷1/4	900MPa	425°C	A286			
	PO140		900MPa	235°C	25CrMo4			
	PO141		900MPa	425°C	A286			
	PO150	4-40÷5/16	900MPa	235°C	25CrMo4	MS21071	NAS696	miniature
	PO151		900MPa	425°C	A286	MS21072	NAS696	
	PO152		1100MPa	235°C	25CrMo4	NAS1776		
	PO153		1100MPa	425°C	A286	NAS1776		
	O150	4÷6	900MPa	235°C	25CrMo4			
	O151		900MPa	425°C	A286			
	O160		900MPa	235°C	25CrMo4	LN29996		miniature, deep c'bore
	O161		900MPa	425°C	A286	LN29996		
JO162	1100MPa	235°C	25CrMo4	EN3712				
JO163	1100MPa	315	A286°C	EN3768	EN4249			
	PF600	4-40÷5/16	900MPa	235°C	25CrMo4	MS21061	NAS687	floating
	PF601		900MPa	425°C	A286	MS21062	NAS687	
	PF602		1100MPa	235°C	25CrMo4	NAS1774		
	PF603		1100MPa	425°C	A286	NAS1774		
	F600	3÷8	900MPa	235°C	25CrMo4	LN29681		
	F601		900MPa	425°C	A286	LN29668		
	F610	3÷10	900MPa	235°C	25CrMo4	LN29987	LN65127	floating, deep c'bore
	F611		900MPa	425°C	A286	LN65006		
	JF620		1100MPa	235°C	25CrMo4	DIN65243	EN2866	
	JF621		1100MPa	425°C	A286	DIN65244	EN2867	
	PF640	10-32÷1/4	900MPa	235°C	25CrMo4			variable deep c'bore
	PF641		900MPa	425°C	A286			
	F640	5÷8	900MPa	235°C	25CrMo4			floating
F641		900MPa	425°C	A286				
	FR610	5÷8	900MPa	235°C	25CrMo4			replaceable
	FR611		900MPa	425°C	A286			
	FR620		900MPa	235°C	25CrMo4			
	FR621	5÷10	900MPa	425°C	A286			deep c'bore
	FR630		1100MPa	235°C	25CrMo4			
	FR631		1100MPa	425°C	A286			